

P400S Post driver



PROTECH



P400S Post driver

P400S configuration

- ✓ 300kg hammer
- ✓ Tele-mast: 12 Feet posts capability
- ✓ Hydraulic counterweight with 800mm sideshift
- ✓ External control levers
- ✓ 800mm telescopic arm
- ✓ 120-degree hydraulic slew
- ✓ 35-degree forward/back mast tilt
- ✓ 35-degree side/side mast tilt
- ✓ Hydraulic rear leg
- ✓ Quick Release 300mm throat width Gripper Plate
- ✓ Reinforced rubber on gripper for noise reduction
- ✓ Independent hydraulic front legs
- ✓ Road lights
- ✓ Drawbar

Options :

- 350 kg hammer weight
- 400 kg hammer weight
- 75 mm rock spike and hydraulic extractor
- Hydraulic 6x3" post twister



Controls

Full hydraulic operation



Hydraulic counterweight
800mm sideshift counterweight. All hydraulic operated.



Rock-spike and Extractor

75mm rock spike to go through rocky grounds, easily operated in and out. Includes the hydraulic extractor for a safe and efficient operation.

One additional lever valve.

Optional.

Drawbar & roadlights

Fitted as standard.



Tele-mast

800 mm telescopic arm for a long reach. Heavy duty construction with wear pads for enhanced lifetime.



PROTECH MACHINERY LTD

Woolridge Farm, Gloucester Road, Hartpury, Gloucester GL19 3BG

Tel: 01452 700713 Email: sales@protechmachinery.com

Company reg. no. 4958012 VAT no. 834 1361 48